Varde Aura 1 Varde Aura 2 Varde Aura 3 Varde Aura 11 Varde Aura 3 Stone

Aura 1, 2, 3, 11 Aura 3 stone	and User Manua Revisior
A++ A+ A	
5,0 kW	
NERGIA - EHEPFUR - ENEPFEIA - ENERGIA - ENERGY - ENERGIE - ENERGI D15/1186	

Pottemagervej 1, 7100 Vejle, Denmark. www.vardeovne.dk

Congratulations on the purchase of your new woodburning stove from Varde.

Wood-burning stoves from VARDE stand on the stylistic bedrock of Scandinavian design – created with the ambition of unifying quality, functionality and design.

With a VARDE stove, you and your family are ensured a warm gathering point and tranquil quality moments for many years into the future.

Henrik Nøhr CEO Varde Ovne A/S

Contents

Welcome and contents	Page	2
Facts about Aura 1	Page	3
Facts about Aura 2	Page	4
Facts about Aura 11	Page	5
Facts about Aura 3 Stone	Page	6
Facts about Aura 3	Page	7
Rules and approvals	Page	8
Floor material and distances	Page	9
Installation distances	Page	10
Chimney	Page	11
Chimney connection to stove	Page	12
How it works	Page	13
How it works	Page	14
How to light up and use your stove	Page	15
Overview of loose parts	Page	16
Vermiculite	Page	17
Choice of wood	Page	18
Maintenance	Page	19
Spare parts	Page	20
How to correct faults	Page	21
Test certificate (RRF)	Page	22
Warranty	Page	23











Important!

Before you install and use your new Varde stove for the first time, we recommend that you first spend a couple of minutes reading this Installation and User Manual.

Inspection of the installation

It is extremely important that the installation is inspected by an authorised chimney inspector before the stove is used for the first time.

This $\ensuremath{\textbf{Varde stove}}$ is approved in accordance with:

European Standard DS/EN 13240/PrEN 16510 German Stufe 2 and Norwegian NS and §15 for Austria and is accordingly certified as having eco-friendly combustion properties.

The stoves are designed for intermittent combustion and are also designed for chimneys with several stoves connected.

Applicable regulations

The installation must comply with all local regulations, including those that refer to national and European standards. Seek advice and guidance from the dealer from which you bought the stove or from a professional installation technician. NB: All Varde wood-burning stoves are closed fires.

Professional installation

We recommend that you seek advice from the dealer you purchased the stove from or from another competent installation technician, as there can be specific details that must be taken into consideration with the installation.

Duty to report

The local chimney inspector has a duty to report.

Before the installation is carried out, the stove must be stored in a dry place at room temperature. The stove does not tolerate moisture.

Please note that your existing chimney may not necessarily be efficient enough for a new, modern wood-burning stove.

EU Declaration of Conformity. MANUFACTURER Name: Varde Ovne A/S Address Pottermagervej 1, 7100 Vejle, Denmark **Fireplace Inspection** Name: RRF Address Im Lopperfeld 34b, 46047 Oberhausen, Germany Product Varde Product type Aura 1, 11, 2, 3 and 3 Stone Type designation Standard Wood-burning stove, suitable for intermittent use Construction product (89/106/EC/) standard used EN 13240 Application Heating of homes Mood Fuel Special conditions None **CE marking** Issued 2017 5.0 kW Nominal output Type of fuel Wood Flue gas temperature 265°C Efficiency 81% CO emissions 0.10% Henrik Nøhr CEO Varde Ovne A/S

General advice and instructions are available on the Varde Ovne website. www.vardeovne.dk

Floor material:

If the stove is to stand on a flammable floor, then the floor area on which it stands must naturally be covered by a non-combustible material, e.g. a steel sheet, glass sheet, tiles or artificial slate sheet. The floor sheet must extend by at least 15 cm out from the sides of the stove and at least 30 cm out from the front. However, we recommend 50 cm in front of the stove

The floor structure must also be able to support the stove and if required, the chimney's total weight.

Stove	Weight in kg
Aura 1	104
Aura 11	113
Aura 2	104
Aura 3	104
Aura 3 Stone	190

Installation distances:

If the wall is non-combustible, the stove may be positioned next to it. However, we recommend that you keep a gap of 5-10 cm, which will mean that you will be able to clean behind the stove. If the chimney cleanout access door is behind the stove, make sure there free access to it and there is enough space to clean the chimney thought it.

Installing the stove in relation to combustible material.

It is recommended that there is a distance of 22.5 cm from the outer edge of the flue to any combustible material. Please note that there may be other national and local regulations relating to the distance to combustible material. Contact your local chimney inspector for advice.

The stove's individual distance to combustible material is shown on page 10 or under the technical data.

Fresh air supply

In the room where the wood-burning stove is to be installed, you must ensure that there is sufficient fresh air supply. Combustion only works effectively when new air is constantly supplied to the fire. This can be achieved, for example, by installing room ventilation valves in the walls. It must not be possible to block these air grates.

The combustion requires airflow of approx. 14-20 m³/h.

Installation distances:

The stove must, in accordance with the applicable regulations, comply with the following minimum distances to combustible walls and materials:

From the sides: 30 cm

Rear: 12.5 cm

Distance to furniture: 80 cm

<u>NB: Note that B (from chimney to the wall) is a recommendation. There may be different local/national rules.</u>

Aura	1.	11.	2.	3	and	3	Stone
,	- /	/		-		-	0.00.10

А	12,5 cm	С	30 cm
В	22,5 cm	D	80 cm

Aura 1 and 11







Aura 2







Aura 3 and Aura 3 Stone







Chimney:

There must always be a chimney stack with a diameter of at least 15 cm. This is equivalent to clearing of 175 cm². Remember to ensure that the **draught conditions** are satisfactory and that smoke does not inconvenience your neighbours.

If your chimney has a regulating damper, the draught can be regulated. Please note that the damper must never be completely closed. There must always be at least 20 cm² of free passage through the chimney.

In some cases, it can be an advantage on days when the wind is blowing strongly.

At nominal operation, the stove has been tested with a flue gas flow of 4.6 g/s and with flue gas temperature of 265° C at a room temperature of 25° C.

Varde stoves are always equipped with a smoke guide plate. This ensures that the smoke's path to the chimney is as long as possible. This ensures that the smoke's heat is released in your home rather than in the open air outside. The smoke guide plate lies loosely in the stove's combustion chamber and you must ensure that the plate is pushed all the way back against the combustion chamber's rear plate.

New chimney

If you shall install a new chimney, it is recommended to consult your local chimneysweeper, as there can be specific local circumstances that can have influence on the height or routing of the chimney. You can find inspiration, and common guideline on www.vardeovne.dk

Is my existing chimney good enough?

The chimney is the motor of the stove, the chimney is driven by heat, so it is important that you have a well function chimney in order for the stove to work properly.

A modern wood burning stove puts up higher demands for the chimney than older stoves. A modern stove burns both cleaner and more efficient than older stoves, the higher efficient will give more heat in your living room for the same amount of firewood. The higher efficiency of a modern stove also have that effect, that there are used less heat to generate draft your chimney.

It can be a possibility that your old chimney will not be able to build up a sufficient draft to run a modern clean burning stove, be course of the lesser heat lead into to the chimney.

This may occur with shorter or older brick chimneys, especially without an insulating core.

It is very rare that a steel chimney or modern insulated brick chimney not will be sufficient.

Typical effects of insufficient draft, smoke come out when door is opened and soot on the glass. If you have a chimney with draft problems, a draft booster could be a solution.

It is recommended that you consult with your local chimneysweeper for more specific advice.

Condensation drain in the flue collar

Your stove is fitted with a cast iron flue collar from Varde Ovne. The flue collar is designed for a flue pipe (chimney) with an inner diameter of 150 mm.

You can establish a condensate drain yourself, if your steel chimney is to be fitted in the stove's top outlet:

Make a hole in the bottom of the exterior grate (at the mark) using a small chisel or similar, thus making the condensate drain yourself, if you need it.

Marking of condensate drain.

Make an opening using chisel or similar.





A condensate drain has now been made.



Connecting the flue:

Connect the stove using the top outlet

Connect the stove using the rear outlet.





Placing cover plate on Aura 3. Bend and adjust the steel threads under the top plate. The steel cover plate are placed in the ashpan on the Aura 3 model.





- 1. Cut the discs out in both back plate layers.
- 2. Unscrew the bolts in the flue collar and facing plate.
- 3. Swap the flue collar and facing
- plate. 4. Screw the bolts in the facing plate and flue collar.
- 5. Put the top plate into position. NB! The cover plate to close the hole in the top plate is not sup**plied.** 6. Fit the flue pipe





Tertiary airflow

is a constant supply of air that ensures the stove burns more cleanly and, among other things, reduces the burning material's content of tar and soot particles to the absolute minimum sizes. With optimal burning you will see that the glass and the combustion chamber will burn completely cleanly and there will be a minimal amount of ash left by the fire.

Combustion air Pre-warmed air for combustion (secondary airflow). It must be adapted in every single case. A strong chimney draught requires less supply of combustion air.



Overheating

Overheating occurs when you put too much wood in the stove or if the fire has too much air. This can happen, for example, when the gaskets in the stove are not sealed or the ash pan has not been closed properly. In extreme cases, overheating can lead to a fire in the chimney. Overheating also causes much wear on the stove, both to wearing parts and gaskets, glass, vermiculite and the stove itself.

How to light up and use your stove:

When you use the stove for the first time, the surface coating will cure and smoke will come from the stove and it will have a slightly pungent smell, which will disappear after a good airing. We therefore recommend that you open the doors and windows so there is airflow to/from outside.

During the curing process, the coating will become soft and vulnerable, so therefore avoid touching the coated surfaces. We also recommend that you regularly open and close the door during the first couple of hours to avoid the door's gasket from becoming stuck to the coating.

Never use flammable liquids such as spirits or petrol when you light the fire!

We recommend that you light the fire using the "Top-Down" method, where you light the wood at the top of the combustion chamber rather than at the bottom. This method is the most eco-friendly way to light a fire. At the same time, it will be easier to keep the glass in the door clean.

Cross 2-4 small pieces of kindling on the combustion chamber's base plate (approx. 0.7–1.1 kg). Position them so that there is a small gap between the individual pieces. On top of these, place 8–12 small wooden pins (0.4–0.7 kg), and place 1-2 kindling blocks on the top and in between the wooden pins. In total, about 1.5 kg wood. It is easier to light the fire if there is a thin layer of ash in the base of the stove.

Before you light the fire, air must flow up through the base grate, and the air rosette in the ash pan for the **kindling air** must be open, and the damper above the door for the combustion air must be drawn to the right so that it is completely open for the **combustion air**. When the fire is burning well, remember to close the kindling air again, since the stove and chimney otherwise can become overheated and the warranty for the stove and chimney will be void. Remember to check that the ash pan has also been closed correctly.

However, in most cases you will need to find the **best setting** for the combustion air yourself, due to: the chimney draught, chimney height, quality of the fuel etc. all this play a crucial role in how your stove operate best.

If the stove's nominal heat output becomes too great in relation to your heating requirements, you can reduce the heat output as follows:

- Use a smaller amount of fuel than normally, e.g. 0.9–1.2 kg and ideally consisting of 2 smaller pieces of wood. Apply full air to light the wood properly, then reduce the combustion air, perhaps down to 30%. However, you must not reduce it so much that it causes the fire to go out. There must always be clear flames.

Using this method, depending on the chimney draught, quality of the fuel, etc., you can reduce the stove's heat output from a nominal 5.0 kW to perhaps 3-3.5 kW.

Note that if you reduce the combustion air too much, this can lead to poor combustion, which will result in reduced efficiency and increased emission value in the smoke (increased pollution).

When re-stoking the fire, we recommend that you first open the door and load new wood when there are only embers left inside the combustion chamber. If there are flames, then smoke and gas are still being generated, and depending on the efficiency of your chimney, there is a danger that smoke downdraught will enter the room.

When re-stoking, use gloves when loading the wood.

If you experience problems with lighting the fire and its function, see the section: How to correct a fault.

To achieve the nominal heat output, below setings is recommended, this may vary as a consequence of the chimney's effectiveness:

First firing amount [kg]	Kindling air [%]	Combustion air [%]	Nominal output [kW]	Chimney - draught [PA]	Efficiency [≥ in %]	Re-stoking interval at nominal output [minutes]
1,3	0 (closed)	approx. 60	5.0	12	81	approx. 45



- Shaker grate Log retainer Vermiculite
- Ash pan
- Cast iron door
- 1. 2. 3. 4. 5. 6. 7. 8. 9. 10. 11. 12.
- Top plate Air rosette for kindling air

- Secondary air damper Throttle for shaker grate Tertiary air beam (tertiary airflow) Flue collar
- Magnet for base cover, can vary depending on model

Vermiculite

The panels in the combustion chamber are known as **vermiculite panels** and they become worn over time. The smoke guide plate also becomes worn. You only need to replace the panels if the crack is more than about ½ cm wide.

Vermiculite

A special fireproof material made of compressed stone granulate, which looks like fibreboard. The panels are insulating and ensure that the stove does not wear out. Vermiculite panels are not covered by the warranty.

Vermiculite is a **very porous** material and must be handled with care.

Only original spare parts from Varde Ovne A/S may be used.



How to replace the vermiculite cladding

- 1. Lift the smoke guide plate/top plate gently and tilt the side up; it can be edged out diagonally.
- 2. Lift the left side plate gently and take out.
- 3. Lift the right side plate gently and take out.
- 4. Remove the bar on the shaker grate; do this by removing the ash pan and lifting the rotating section of the cast iron base on the left side. You can then remove the bar from the shaker grate through the hole.
- Push the cast iron base right to the back of the stove and lift at the front, allowing the rear plate to slide free.

To fit, repeat the procedure in reverse.

Which wood is the best?

In general, beech is the best wood for a fire. It burns evenly and produces very little smoke and the ash is clean and does not take up much space. Ash, maple and birch are also suitable alternatives.



How big do the pieces of wood have to be?

Wood with a diameter that is greater than 8-10 cm should be chopped into smaller pieces. The logs must be 20-25 cm in length. Using larger amounts of firewood than stated in the table on the bottom of the page, will load the stove with heat that is higher than it is designed for, which will cause a higher temperature in the chimney and lower efficiency.

This can result in the chimney being damaged, and the warranty will be void.

Kindling sticks

Length: 20–25 cm Size 3x3 cm Normal amount: 10–15 sticks (approx. 1.5 kg)

Logs

Length: 25-30 cm Diameter: max. 10 cm Normal amount: 2 logs (approx. 1.3 kg)

Your new stove

When you use the stove for the first time, the surface coating will cure and smoke will come from the stove and it will have a slightly pungent smell, which will disappear after a good airing. We therefore recommend that you open doors and windows so there is airflow to/from outside. During the curing process, the coating will become soft and vulnerable, so therefore avoid touching the coated surfaces. We also recommend that you regularly open and close the door during the first couple of hours to avoid the door's gasket from becoming stuck to the coating.

What can you make a fire with?

This **Varde stove** has been approved and tested for the combustion of wood. Only dry wood may be used with a max. water content of 21% and a size that is suitable for the combustion chamber. If you use wet wood, it will produce a lot of tarry soot, pollute the outdoor air and your stove will have a poor fuel economy. Wood from newly felled trees contains approx. 60–70% water, and it is completely unsuitable for use in fires. You should expect that wood from newly cut trees will have to be stored under a roof for at least 12 months to dry before it can be used in the stove.

Do not use! - Take care of the environment

Similarly, you must **never** fire your stove with wood that is toxic when burned, such as glulam, particle board, painted or laminated wood. If you fire your stove with these completely unsuitable materials, it will change the combustion properties, which will affect the stove's output and can result in overheating of the stove and the warranty will be void. In addition, the burning of this kind of material will lead to emissions of very unpleasant smoke with extremely high levels of pollution.

Top-down method to light fire

Do not stack the fire wood higher than shown on page 14.



Maintenance:

As with anything else that you use on a daily basis, your stove must of course be maintained. You should only clean your stove when it is cold. Wipe the outside using a dry cloth, do not use water or cleaning detergents, it will wear out the heat resistant paint on the stove very fast. You should as well clean it regularly on the inside. The actual combustion chamber should be cleaned of ash and soot remnants. You should also remove the smoke guide plate, because dirt and soot will build up behind it, and check that there is free access through the flue and chimney. You should also check that the gaskets in the door and ash pan are not worn out. If the gaskets do not seal properly, they must be replaced. Remember to lubricate the door hinges as required.

Glass

We recommend the use of VARDE glass cleaner to clean the pane; this can be bought from our dealers.

The **ash pan** must be emptied regularly, and the ash can be disposed of along with your domestic waste. But you must of course make sure that the ash does not contain any embers. If you are unsure about how to clean or maintain your wood-burning stove, contact the dealer who sold you the unit or contact your chimney inspector.

In particular, following a long period of time where you have not used the stove, before using it again you must make sure that there is nothing blocking the flue or the chimney.

Some exposed areas of the **stove's painted surface** can over time become worn out e.g. through cleaning or overheating of the wood-burning stove. However, this can be repaired using a special coating, Senotherm®, which comes in a spray can and can be purchased from your dealer.

The **panels in the combustion chamber** are known as **vermiculite panels** and will become worn over time. If a piece of wood damages a vermiculite panel, it has no effect on combustion. You do not need to replace the panels unless the crack in the panel is more than about 1/2 cm wide.

Only original spare parts from Varde Ovne A/S may be used.

The door is fitted on a lock spring, which pulls the door in. This is a regulatory requirement in certain countries. The spring is attached to the hinge, and can be removed if you do not wish to have a spring-loaded door.

No unauthorised alterations may be made to the wood-burning stove.

All of the exterior parts of the wood-burning stove will become very hot during use. You should therefore exercise necessary caution.

IMPORTANT!! Chimney fires

If your chimney catches fire, you must follow this procedure:

- Close all of the air supplies to the stove and telephone 112.

(Most chimney fires will go out on their own once you have stopped any air from getting into the stove).

As a minimum, you must contact your chimney inspector, who will then inspect the stove and chimney for damage.

Log retainer, product no. and EAN number Aura 1 and 11 : 100483 / 5703505042920 : 100477 / 5703505601110 Aura 2 and 3 Top Cover, product no. and EAN number Aura 3 and 3 Stone : 100701 / 5703505049233 (Steel Ø165 VO logo) Aura 1, 11 and 2 : 100266 / 5703505033546 (Cast iron) Glass, product no. and EAN number Aura 1 and 11 : 100280 / 5703505042722 Aura 2 and 3 : 100281 / 5703505042739 Handle, product no. and EAN number : 100402 / 5703505042142 Aura 1 and 11 Aura 2 : 100404 / 5703505042159 : 100408 / 5703505043668 Aura 3 Ash pan, product no. and EAN number . Aura 1, 2, 3 and 11 : 100712 / 5703505044382 Set of vermiculite panels, product no. and EAN number : Including smoke quide plate Aura 1 and 11 : 100309 / 5703505042814 Aura 2 and 3 : 100318 / 5703505038831 Gasket for glass and ash pan, product number and EAN number 100443 / 5703505045457 Gasket for door incl. glue, product number and EAN number: 100351 / 5703505040162 Glass cleaner spray, product number and EAN number: 100493 / 5703505045471 Repair spray for paint Black 400 ml: 100603 / 5701909002069 Grey 400 ml : 100604 / 5701909006142

How to correct a fault.

Smoke entering room

- Poor draught in the chimney.
- Check that the flue and chimney are not blocked.
- Check that the chimney height is correct in accordance with the surroundings.

Glass and/or chimney soot:

- Wood is too wet.
- There is insufficient combustion air (secondary air).
- You have closed the kindling air too quickly when you started the fire.
- There must always be clear flames in the combustion chamber.

The stove is not heating the room:

- The wood is too wet (all the energy is being used up in drying the wood) or the wood is poor quality.
- Check that the smoke guide plate is positioned correctly (free passage for smoke).
- Insufficient combustion air (secondary air).

The fire burns too intensely:

- The gasket in the door or ash pan does not seal (it must be replaced).
- The chimney draught is too powerful (fit a damper in the chimney).
- Check that the kindling air is closed.

The shaker grate is stuck:

- Check that a piece of wood or similar is not stuck in the grate.
- Check that the shaker grate bar is in the correct position.

Recycling

Packaging

In consideration of the environment, the packaging should be disposed of in accordance with local regulations for the disposal of waste. The packaging is 100% recyclable.

Ceramic glass

Ceramic glass must be taken to the local recycling station and recycled with other ceramics and porcelain, where it is sent to a waste disposal facility.

Vermiculite

Vermiculite panels from the stove must be taken to the recycling station, where they will be sent to a waste disposal facility

Rhein-Ruhr Feuerstätten Prüfstelle • Im Lipperfeld 34 b • 46047 Oberhausen

- Anerkendt prøveinstitut, godkendt af Europakommissionen (EU) Nr. 305/2011, notified body: 1625
- Proveinstitut efter DIN EN ISO/IEC 17025:2005, DAkkS Nr. D-PL-17727-01-00
- Anerkendt prøveinstitut i h. t. Deistatsbyggevedtægterne, reg.nr.: NRW 15
- Anerkendt prøveinstitut for byggetilsynsmæssige tilladelser
- ♦ Anerkendt DIN CERTCO proveinstitut, reg.nr.: PL139





PRØVNINGSATTEST

| Kontrolerklæring nr | RRF - DK 17 4484 | | | |
|--------------------------|---|--|--|--|
| Prøvens art | Prøve i h. t. EN 13240:2001/A2:2004/AC:2007 | | | |
| Ordregiver: | Varde Ovne A/S | | | |
| | Soldalen 12, DK-710 | 00 Vejle | | |
| Genstand for prøven: | brændeovn | | | |
| | Aura 1 | | | |
| | Aura 2, Aura 3, Aur | a 11, Aura 12 | | |
| Nominel varmeydelse: | 5,0 kW | | | |
| Emissioner i forbrænding | sprodukterne relatere | at til 13 % O2. | | |
| CO-emissionen | 0,10 % | | | |
| Støvemissionen: | 21 mg/m ^a | efter CEN/TS15883, Annex A. 1 (DINplus metode) | | |
| OGC | 97 mg/m³ | efter CEN/TS15883, Kapitel 4 | | |
| Virkningsgrad: | 81 % | | | |
| CVR nr.: | 21554979 | | | |
| P-nr.: | 1005018532 | | | |
| Prøvningsresultater: | Det attesteres herved at ovenfor nævnte fyringsanlæg opfylder
emissionskravene i: Bilag 1 til bekendtgørelse nr. 46 af 07/12/2015 vedr.
regulering af luftforurening fra fyringsanlæg til fast brændsel under 1 MW
(1. og 2. trin) | | | |

Bemærk venligst, at de oplyste værdier er uddrag af prøvningsrapporten.

| Godkendelsesa | fdelingens leder |
|---------------|------------------|
| 111 | 9 11 |
| 1 LAis | - Loll |
| (C Droll) | 2001 |
| Oberhausen, | 21.03.2017 |

Skorstensfejer påtegning

Dato,

underskrift

Warranty

All **Varde stoves** undergo substantial quality control, and we take pride in supplying the same high quality at all times. We do, however, offer a **5-year warranty** for any manufacturing defects, should they occur.

The warranty does not cover:

- Wearing parts, vermiculite panels in the combustion chamber, glass, handles, gaskets, cast-iron base and shaker grate.
- Damage there is the result of incorrect operation, e.g. overheating, unapproved fuel, incorrect connections, lack of or incorrect maintenance, etc. (see these user instructions).
- Damage caused by external effects of a physical nature.
- Transportation costs in connection with any warranty repair.
- Installation/dismantling during the warranty period.
- Compensation for any consequential damage, including damage to other items.

All enquiries regarding complaints must be made through the dealer where the stove was purchased.

When making a complaint, make sure that the complaint includes pictures, the purchase receipt and the 16-figure serial number, which is on the rear of the stove.



Pottemagervej 1, 7100 Vejle, Denmark. www.vardeovne.dk